

Continuous Band Sealer - Dual Heat Zones



VALUE, VERSATILTY AND RELIABILITY

Elevation Packaging & Equipment, Inc.

402-740-1512 www.elevationpkg.com

The Dual Continuous Band Sealer is designed for performance and reliability in the harshest of environments. Built for multiple shift operations with minimal maintenance and ease of set-up, and is constructed of only the highest quality components.

The Dual Heat Zone Continuous Band Sealer Offers the following features:

- Heavy duty construction
- More heat than comparable models
- **■** DC Variable Speed Drive
- Easy band replacement
- Nickel Plated Sealing Head
- Solid State Temperature Control
- Designed for automatic or manual lines
- Carrier belts for bag top control
- Heat and Cool Bars hardened for a longer life
- 220 V single phase
- **■** User Friendly

OPTIONS

- Bag Top Trimmer
- Code Date Systems
- Casters
- Stainless Steel Construction
- Special Seal Width
- Nema 4
- Annodized and Stainless Construction

SPECIFICATIONS

Sealing Speed: up to 80 fpm

Heat Bars: 4 pcs. 8" long

Total 16" heat

Cool Bars: air or water

Sealing Bands: Teflon* Fiber

Seal Width: .25", .375", .50"

Products: all heat sealable bags,

tube or gusseted style

Machine Weight: 850 lbs

Machine Length: 69"

Machine Width: 36" Seal Height: 36" to 58"

Feed Direction: Right to Left



